

IN THE CLAIMS:

Please amend the claims to read as follows:

Claim 1 (Currently Amended): A part clamp to be affixed fixed and nailed to a surface by a nailing machine, comprising:

- a base portion;
- a through hole formed at a center of the base portion for inserting a nail thereinto;
- a rising portion rising from the base portion; and
- an engaging portion engageable with a leading end of a nailing machine.

Claim 2 (Original): The part clamp according to claim 1, wherein the engaging portion is formed on the rising portion in a lip shape and elastically deformable.

Claim 3 (Withdrawn): The part clamp according to claim 1, wherein the engaging portion is a rod-shaped member protruding vertically from the base portion.

Claim 4 (Withdrawn): The part clamp according to claim 1, wherein the engaging portion is formed to protrude vertically from the base portion and has a protrusion protruding toward the through hole.

Claim 5 (Withdrawn): The part clamp according to claim 1, wherein the engaging portion is formed in a lip shape and has an inner edge portion formed in a noncircular shape.

Claim 6 (Withdrawn): The part clamp according to claim 1, further comprising:
a guide face inclined on an inner wall face of the rising portion.

Claim 7 (Withdrawn): A part clamp to be fixed by a nailing machine, comprising:
a base portion;
a through hole formed at a center of the base portion for inserting a nail therein; and
an engaging portion engageable with a leading end of a nailing machine by pushing the
part clamp toward the leading end of the nailing machine in an opposite direction of a nail
striking direction.

Claim 8 (Withdrawn): A nailing machine comprising:
an injection port;
a contact arm arranged slidably along the injection port; and
a short cylindrical portion disposed at a front end of the contact arm for temporarily
holding a part clamp to be fixed with a nail by a nailing machine,
wherein the part clamp includes a base portion, a through hole formed in the base portion
for inserting a nail therein, and an engaging portion engageable with the short cylindrical
portion by pushing the part clamp in an axial direction of the injection port, and
a load to push the part clamp into engagement with the short cylindrical portion is lower
than a load for pushing the contact arm to slide along the injection port.

Claim 9 (Withdrawn): The nailing machine according to claim 8, further comprising:
an annular protrusion formed at an outer circumference of the short cylindrical portion,
wherein the engaging portion is formed in a lip portion elastically engageable with the annular
protrusion.

Claim 10 (Withdrawn): The nailing machine according to claim 8, further comprising:
a groove portion formed in an outer circumference of the short cylindrical portion and in
parallel with an axial direction of the injection port, wherein the engaging portion is formed in a
rod shape vertically protruding from the base portion and can be fitted in the groove portions.

Claim 11 (Withdrawn): The nailing machine according to claim 8, further comprising:
an annular groove portion formed in an outer circumference of the short cylindrical
portion, wherein the engaging portion vertically protrudes from the side of the base portion and
elastically engageable with the annular groove portion.

Claim 12 (Withdrawn): The nailing machine according to claim 8, wherein the short
cylindrical portion has a noncircular outer circumference, and
the part clamp come into engagement with the short cylindrical portion by relatively
rotating the short cylindrical portion and the part clamp, after the part clamp is moved in an axial
direction of the injection port till a leading end of the short cylindrical portion and the base
portion are contact with each other.